



## Type of luminaire

Photometric body	Uncovered light, partly covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120 °.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max ø12.
Type of light source	LED E27 lamp
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	4,45kg / 4,85kg

## Technical data

LED E27 lamp	Philips Master LEDbulb A60 8,5W<=>60W E27
Light source wattage	LED 8,5W
Luminaire wattage	8,5W
Lamp luminous flux	~ 806lm
Luminaire luminous flux	805lm
Light source efficiency	94,8lm/W
Efficiency of the luminaire	94,7lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Energy Efficiency Index	<b>A+</b>
Power Factor luminaire	PF>0,7
Ta Rated temperature	+25°C

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

## Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

## Spare parts

06281004	Lens.
08288004	Gasket.

## Files to download

Manual

## Indexes

Index	Color	RAL
1269B	BLACK	9005
1269GA	GALVANIZED	-