



## Type of luminaire

Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Wood - scandinavian impregnated pine and hot-dip galvanized steel. Wood - scandinavian impregnated pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing$ 9mm with a diameter of $\varnothing$ 65mm every 120°.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max $\varnothing$ 12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	5,9kg / 7,3kg
Box dimensions [cm]	20,5x20,5x91

## Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Energy Efficiency Index	<b>A+</b> <b>D</b>
Ta Rated temperature	+25°C

Possibility to order luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.
46999021	LED E27 lamp

## Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

## Spare parts

06291001	Lens.
08288004	Gasket.

## Files to download

Photometric LDT files	Photometric IES files
3D models and drawings	Manual

## Indexes

Index	Color	RAL
1443B	BLACK	9005
1443GA	GALVANIZED	-