



Type of luminaire	
Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information	
Materials	Wood - scandinavian impregnated pine and hot-dip galvanized steel. Wood - scandinavian impregnated pine, hot-dip galvanized and powder painted steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing$ 9mm with a diameter of $\varnothing$ 65mm every 120°.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max $\varnothing$ 12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	4,65kg / 5,7kg
Box dimensions [cm]	20x20x55

Technical data	
E27 lamp	QA55 / LED A55..60
Light source wattage	MAX 46W / LED 9W
Energy Efficiency Index	A+ D
Ta Rated temperature	+25°C

Possibility to order luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimnable).

Accessories <small>sold separately</small>	
205ZX0010	Concreting anchor.
206GA0010	Anchoring support.
206GA0S10	Ground anchor.

Recommended light sources	
Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts	
06291001	Lens.
08288004	Gasket.
46999021	LED E27 lamp.

Files to download	
Photometric LDT files	Photometric IES files
3D models and drawings	Manual

Indexes		
Index	Color	RAL
1453B	BLACK	9005
1453GA	GALVANIZED	-