STOCKHOLM 1464

220-240V 50-60Hz | IP 65 | E27

Stockholm 1464XX0012
11.10.2019 v.12.3
www.norlys.com



Type of luminaire

Type of lumianire	Bollard.
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120 °.
Terminal	Connection terminals: max 3x2,5mm², possibility to connect luminaire in loop max 3x2,5mm². A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	LED E27 lamp
Net / gross weight of luminaire	9,75kg / 11,05kg
Box dimensions [cm]	15x15x91

Technical data

LED E27 lamp	Philips Master LEDbulb 806lm/8,5W/2700K (ściemnialna)
Light source wattage	8,5W
Luminaire wattage	8,5W
Lamp luminous flux	~ 806lm
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	25 000h
Energy Efficiency Index	A+
Power Factor luminaire	PF 0,7
Ta Rated temperature	+25°C

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
46999021	LED E27 lamp.

Recommended light sources

Osram LED Parathom Classic E27 — Philips Master LEDbulb / Ledbulb Classic E27

Spare parts

06281004	Lens.
08120001	Gasket.

Files to download

Manual

Indexes

Index	Color	RAL
1464B	BLACK	9005
1464GA	GALVANIZED	-

Norlys AS
P.B 1014 Hoff, 0218 Oslo
Hovfaret 4B, 0275 Oslo
Norway
+47 24 12 40 11
firmapost@norlys.no

TÜVRheinland CERTIFIED Management System ISO 9001:2015 IATF 16949:2016 www.tuv.com ID 9108651873
PCC Cert CERTIFICATE ISO 14001
RoHS 2011/65/UE

Please read the manual before installing. Due to the dynamic development of lighting technology, additional information is available upon request. LED module must be replaced by a qualified person in accordance with applicable regulations. Condensation, which can occur in luminaires, is a natural phenomenon and does not impair the quality of the luminaire.