



Type of luminaire	
Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	A bollard luminaire with a stable and durable structure. For lighting private areas and public areas

General information	
Materials	Hot-dip galvanized steel. Hot-dip galvanized and powder-coated steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire : 3 holes ø9mm in diameter ø65mm every 120 °. Other accessories must be purchased separately
Terminal	Connection terminals: max 3x2.5mm ² , possibility to connect the luminaire in loops, max 3x1.5mm ² . Cable in a round wire with a maximum diameter of ø12.5mm
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Box dimensions [cm]	21x21x57

Technical data	
LED module	Lumens EDC 47C 10W xxx 230V A Ver.1.2 (Datasheet)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1098lm
Luminaire luminous flux	159lm
Light source efficiency	109,8lm/W
Efficiency of the luminaire	15,9lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
LED photobiological threat	RG0 or RG1
Energy Efficiency Index	A++
Power Factor luminaire	PF > 0,99
THD factor	< 20%
Ta Rated temperature	+25°C
Max ambient temperature	- 35...+25°C
Inrush current	43mA / 60ms

Accessories <small>sold separately</small>	
205ZX0010	Concreting anchor
206GA0010	Ground anchor

Files to download	
Photometric LDT files	Photometric IES files
Manual	

Indexes		
Index	Color	RAL
1476B	BLACK	9005
1476GA	GALVANIZED	-