



Type of luminaire

Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes ø9mm with a diameter of ø65mm every 120°.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x2,5mm ² . A round wire in the isolation with a diameter of max ø12,5mm.
Type of light source	LED E27 lamp
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	6,7kg / 6,7kg
Box dimensions [cm]	21x21,5x92

Technical data

LED E27 lamp	Philips Master LEDbulb A60 8,5W<=>60W E27
Light source wattage	8,5W
Luminaire wattage	8,5W
Lamp luminous flux	806lm
Luminaire luminous flux	100lm
Light source efficiency	94,8lm/W
Efficiency of the luminaire	11,8lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	25 000h
Energy Efficiency Index	A+
Power Factor luminaire	PF 0,70
Ta Rated temperature	+25°C

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Recommended light sources

Osram LED Parathom Classic E27 Philips Master LEDbulb / Ledbulb Classic E27

Spare parts

06291001	Lens.
08288004	Gasket.
46999021	LED E27 lamp.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
1477B	BLACK	9005
1477GA	GALVANIZED	-