



## Type of luminaire

Type of luminaire	Bollard.
Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 65\text{mm}$ every $120^\circ$ .
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$ , possibility to connect luminaire in loop max $3 \times 2,5\text{mm}^2$ . A round wire in the isolation with a diameter of max $\varnothing 12,5\text{mm}$ .
Type of light source	LED E27 lamp Replaceable (LED only) light source by an end-user.
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	6,7kg / 6,7kg
Box dimensions [cm]	21x21,5x92

## Technical data

LED E27 lamp	Philips Master LEDbulb A60 8,5W<=>60W E27
Light source wattage	8,5W
Luminaire wattage	8,5W
Lamp luminous flux	806lm
Luminaire luminous flux	100lm
Light source efficiency	94,8lm/W
Efficiency of the luminaire	11,8lm/W
Color temperature	2700K
Colour consistency (McAdam ellipse)	SDCM6
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	25 000h
Power Factor luminaire	PF 0,70
Ta Rated temperature	+25°C

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

## Recommended light sources

Osram LED Parathom Classic E27      Philips Master LEDbulb / Ledbulb Classic E27

## Spare parts

06291001	Lens.
08288004	Gasket.
46999021	LED E27 lamp.

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM ArchiCAD

## Indexes

Index	Color	RAL
1477B	BLACK	9005
1477GA	GALVANIZED	-