



## Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire. For lighting private areas and public spaces.

## General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: 2 holes $\varnothing 5\text{mm}$ , spacing 164x242mm.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter $\varnothing 7\text{...}10,5\text{mm}$ .
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,8kg / 3,1kg
Box dimensions [cm]	35x27x9,5

## Technical data

LED module	LUMENS LED DLM90C/230V/A 830
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1100lm
Luminaire luminous flux	387lm
Light source efficiency	110lm/W
Efficiency of the luminaire	38,7lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF >0,90
Ta Rated temperature	+25°C
Inrush current	150mA/500 $\mu\text{s}$

## Spare parts

06524002	Lens.
ZS1620zx0012	Service set.

## Files to download

Photometric LDT files	Photometric IES files
Manual	

## Indexes

Index	Color	RAL
1620AL	ALUMINIUM	9006
1620GR	GRAPHITE	7016