



Type of luminaire	
Type of luminaire	In-ground luminaire.
Photometric body	Four side light distribution covered from the top.
Characteristics of the luminaire	Indicative luminaire or as a spotlight on which you can ride with pneumatic tires. Luminaires should not be used on the road lanes, where they would be exposed to horizontal loads as a result of sudden braking, acceleration, and change of direction

General information	
Materials	Powder painted aluminum cast. Lens - satin polycarbonate, UV stabilized . Silicone gasket. Nickel plated brass cable gland.
Mounting method	Installation: the mounting box should be embedded in the ground in accordance with the instructions Other accessories must be purchased separately
Terminal	The luminaire is equipped with a 3m long H05RN-F 3G1 cable To be connected in a properly selected connection box The maximum load of the luminaire is 1000 kg
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	1,06kg / 1,28kg
Box dimensions [cm]	15,5x15,5x21,5

Technical data	
LED module	Lumens EDC 38C 8W xxx 230V A101 3K (Ⓞ Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	8W
Luminaire wattage	8W
Lamp luminous flux	880lm
Light source efficiency	110lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF 0,99
THD factor	20%
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class  /  EPREL

Optionally, the luminaire is also available:

- For the LED color 2700K [1/1]
- For a different color of the fitting (according to the RAL color palette)

Terms of sale and other information, after contact with the Sales Department of Norlys

Inrush current	35mA / 60ms
----------------	-------------

Accessories <small>sold separately</small>	
139ZX0009	Keramzyt 250ml
142ZX0009	Earthen assembly module
143ZX0009	Power cord cover
145ZX0009	Hermetic box IP68 3-track
146ZX0009	Hermetic box IP68 8-track

Spare parts	
ZS1774zx0009	Service set.

Files to download	
3D models and drawings	Manual

Indexes		
Index	Color	RAL
1774B	BLACK	9005
1774GR	GRAPHITE	7016