



Type of luminaire

Photometric body	Light with rotationally symmetrical light distribution, covered from the top.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes \varnothing 9mm with a diameter of \varnothing 65mm every 120°.
Terminal	Connection terminals: max 3x4mm ² , possibility to connect luminaire in loop max 3x2,5mm ² . A round wire in the isolation with a diameter of max \varnothing 12,5mm.
Type of light source	E27 lamp
Net / gross weight of luminaire	5,28kg / 6,31kg
Box dimensions [cm]	20x20x55

Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	Max 46W / LED 9W
Energy Efficiency Index	A+ D
Ta Rated temperature	+25°C

Possibility to order luminaire with LED E27 lamp Philips Master LEDbulb 806lm / 8,5W / 2700K (dimmbable).

Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	anchoring support.
46999021	LED E27 lamp.

Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

Spare parts

06291001	Lens.
08288004	Gasket.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes

Index	Color	RAL
293B	BLACK	9005
293GA	GALVANIZED	-