



## Type of luminaire

Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

## General information

Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing 9\text{mm}$ with a diameter of $\varnothing 56\text{mm}$ every $120^\circ$ .
Terminal	Connection terminals: max $3 \times 2,5\text{mm}^2$ . A round wire in the isolation with a diameter of max $\varnothing 1,2\text{mm}$ .
Type of light source	E27 lamp
Net / gross weight of luminaire	4,45kg / 4,85kg
Box dimensions [cm]	32x20x20

## Technical data

E27 lamp	QA55 / LED A55..60
Light source wattage	max 46W / LED 9W
Energy Efficiency Index	A+ D
Ta Rated temperature	+25°C

## Accessories sold separately

205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

## Recommended light sources

Osram LED Parathom Classic E27	Philips Master LEDbulb / Ledbulb Classic E27
Osram ECO PRO Classic 46<=>60W E27	Philips ECO Classic 42<=>60W E27

## Spare parts

06281004	Lens.
08288004	Gasket.

## Files to download

Photometric LDT files	Photometric IES files
-----------------------	-----------------------

## Indexes

Index	Color	RAL
299B	BLACK	9005
299GA	GALVANIZED	-