



Type of luminaire

Type of luminaire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	2,22kg / 2,56kg
Box dimensions [cm]	30,5x30,5x11

Technical data

LED module	Philips Fortimo DLM ES 2000/840 G2
Light source wattage	17,5W
Luminaire wattage	17,5W
Lamp luminous flux	2050lm
Luminaire luminous flux	1358lm
Light source efficiency	117,1lm/W
Efficiency of the luminaire	77,6lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Power Factor luminaire	PF>0,90
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class **D**

Inrush current 3,01A/32,66µs

Maximum number of luminaires of this type per MCB:

B 10A: 81, **B 16A:** 130, **C 10A:** 135, **C 16A:** 221

Spare parts

06720003	Lens.
ZS5017zx0014	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
5017AL	ALUMINIUM	9006
5017GR	GRAPHITE	7016
5017W	WHITE	9003