



Type of luminaire	
Photometric body	Uncovered, diffused light with rotationally symmetrical light distribution.
Characteristics of the luminaire	Bollard luminaire of stable and durable construction. For lighting private areas and public spaces.

General information	
Materials	Hot-dip galvanized steel. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: 3 holes $\varnothing$ 9mm with a diameter of $\varnothing$ 65mm every 120°.
Terminal	Connection terminals: max 3x4mm <sup>2</sup> , possibility to connect luminaire in loop max 3x2,5mm <sup>2</sup> . A round wire in the isolation with a diameter of max $\varnothing$ 12,5mm.
Type of light source	LED module AC integrated
Light control	Phase-dimming (TRIAC).
Net weight of luminaire	13,35kg
Box dimensions [cm]	15x15x91

Technical data	
LED module	EDC/47C/10W/840/230V/A001 Ver2.0
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	940lm
Light source efficiency	94lm/W
Color temperature	4000K
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Energy Efficiency Index	<b>A+</b>
Power Factor luminaire	PF 0,99
Ta Rated temperature	-30...+25°C
Inrush current	46,1mA/500 $\mu$ s

Accessories <small>sold separately</small>	
205ZX0010	Concreting anchor.
206GA0010	Ground anchor.
206GA0S10	Anchoring support.

Spare parts	
06295000	Lens.
08295000	Gasket.
46999393	LED module.

Files to download	
Manual	

Indexes		
Index	Color	RAL
5022B	BLACK	9005
5022GA	GALVANIZED	-
5022GR	GRAPHITE	7016