



Type of luminaire	
Type of luminaire	Recessed wall luminaire.
Photometric body	Covered light facing down.
Characteristics of the luminaire	Luminaire designed to illuminate stairs, steps, staircases, communication lines and many other applications.

General information	
Materials	Powder painted aluminum cast. Lens - safety glass, milky colour. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: wall-mounted - hole 258x112x115, fixing in the layered wall - hole 235x96x82.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter ø7...10,5mm.
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	1,63kg / 1,78kg
Box dimensions [cm]	27x12,5x11,5

Technical data	
LED module	Philips FORTIMO DLM FLEX 1100/840 G2
Driver	Philips Xitanium 8W 0.2A 40V TE SC 230V
Light source wattage	6,8W
Luminaire wattage	7,4W
Lamp luminous flux	1061lm
Light source efficiency	156lm/W
ULOR	2%
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>60 000h
Energy Efficiency Index	A++
Power Factor luminaire	PF>0,90
Ta Rated temperature	+25°C
Inrush current	1,65A/16,5µs

Maximum number of luminaires of this type per MCB:
B 10A: 160, B 16A: 254, C 10A: 264, C 16A: 431

Spare parts	
06152000	Lampshade.
08154000	Gasket.
46999607	LED module.
46999610	Power supply.

Files to download
Manual

Indexes		
Index	Color	RAL
5025AL	ALUMINIUM	9006
5025GR	GRAPHITE	7016