

Type of luminaire


Type of luminaire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.

General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	2,47kg / 2,82kg
Box dimensions [cm]	30,5x30,5x11

Technical data

LED module	Philips Fortimo DLM ES 2000/8xx G2 3K (☞ Datasheet)
Light source wattage	17,5W
Luminaire wattage	17,5W
Lamp luminous flux	1950lm
Luminaire luminous flux	1249lm
Light source efficiency	111,4lm/W
Efficiency of the luminaire	71,4lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
THD factor	30 %
Ta Rated temperature	+25°C

This product contains light source of energy efficiency class  / EPREL

Inrush current	3,01A/32,66µs
----------------	---------------

Spare parts

06720003	Lens.
ZS5041zx0012	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

Indexes

Index	Color	RAL
5041AL	ALUMINIUM	9006
5041GR	GRAPHITE	7016
5041W	WHITE	9003