



## Type of luminaire

Type of luminaire	Recessed wall luminaire.
Photometric body	Covered light facing down.
Characteristics of the luminaire	Luminaire designed to illuminate stairs, steps, staircases, communication lines, ceiling illumination and many other architectural applications.

## General information

Materials	Front - hot-dip galvanized steel. Body - powder painted aluminum cast Lens - safety glass, satin. Silicone gasket. EPDM cable gland.
Mounting method	Fixing of the luminaire: wall-mounted - hole 258x112x115, fixing in the layered wall - hole 235x96x82.
Terminal	Connection terminals: max 3x2,5mm <sup>2</sup> , possibility to connect luminaire in loop max 3x1,5mm <sup>2</sup> . A round wire in the isolation with a diameter of $\varnothing$ 7...10,5mm.
Type of light source	LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Trailing edge dimming
Box dimensions [cm]	27x12,5x11,5

## Technical data

LED module	Philips Strip 0.5ft 550lm 840 FC HV4
Driver	Philips Xitanium 7W 0.35A 20V TE SC 230V
Light source wattage	4W
Luminaire wattage	5,2W
Lamp luminous flux	683lm
Light source efficiency	170,8lm/W
Color temperature	4000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Power Factor luminaire	PF > 0,96
Ta Rated temperature	+25°C
Inrush current	1A/15,2 $\mu$ s

## Spare parts

46999608	LED module.
46999746	Power supply.

## Files to download

Manual

## Indexes

Index	Color	RAL
5116GA	GALVANIZED	-