



Type of luminaire

Characteristics of the luminaire Modern design luminaire mounted on a telescopic lighting pole with a cap diameter Ø60mm. Other accessories have to be ordered separately.

General information

Materials	Powder painted aluminum cast. Lens - plastic PMMA in milky color. Silicone gasket.
Mounting method	Fixing of the luminaire: luminaire adjusted to Ø60mm lighting pole, depth 95mm.
Terminal	H05RN-F 3G1 cable 6m long, for connection in an appropriately selected electrical installation box.
Type of light source	LED module, power supply
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	4,92kg / 6,54kg
Box dimensions [cm]	22x54,5x54,5
Side area of luminaire	0,042m ²

Technical data

LED module	Cree JK3030 DK190804VA03 (Datasheet)
Driver	Philips Xi BP 40W 0.3-1.0A S 230V C123_sXt (Datasheet)
Driver durability	100000h
Light source wattage	27,2W
Luminaire wattage	32W
Lamp luminous flux	4180lm
Luminaire luminous flux	2996lm
Light source efficiency	153,7lm/W
Efficiency of the luminaire	93,6lm/W
ULOR	0%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>72 000h
LED photobiological threat	RG0 or RG1
Energy Efficiency Index	A++
Power Factor luminaire	PF 0,98
THD factor	9%
Overvoltage	6 / 10kV
Ta Rated temperature	+25°C
Max ambient temperature	-30 ... + 25°C
Inrush current	19A / 210µs

Accessories sold separately, xx - color of the luminaire

3004XX0009	Telescopic lighting pole with adjustable height 3600 ... 4500mm, mounting cap Ø76
3005XX0009	Telescopic lighting pole with adjustable height 3600 ... 4500mm, mounting cap Ø76. Concreting anchor included.
7661ZX0009	Electric box
7663ZX0009	Concreting anchor
7664ZX0009	100 kg concrete foundation for mounting lighting pole.
7665XX0009	Reduction for Ø60 luminaire to install on Ø76 lighting pole.

Spare parts

4699101105	LED module.
4699200102	Power supply.
ZS6150ZX0009	Service set.

Files to download

Photometric LDT files	Photometric IES files
Manual	

Indexes		
Index	Color	RAL
6151AL	ALUMINIUM	9006
6151GR	GRAPHITE	7016