



## Type of luminaire

Type of luminaire	Wall/ceiling luminaire.
Photometric body	Diffused, uncovered light.

## General information

Materials	Powder painted aluminum cast. Lens - milky polycarbonate, UV stabilized. Silicone gasket. EPDM cable gland.
Type of light source	LED module AC integrated Replaceable (LED only) light source by a professional.
Light control	Phase-dimming (TRIAC).
Net / gross weight of luminaire	2,5kg / 2,5kg
Box dimensions [cm]	30,5x30,5x11

## Technical data

LED module	Lumens DLM 90C 10W xxx 230V /A V0.1 (🔗 Datasheet)
External control	Dimmers Lumens LED AC (User manual)
Light source wattage	10W
Luminaire wattage	10W
Lamp luminous flux	1100lm
Luminaire luminous flux	598lm
Light source efficiency	110lm/W
Efficiency of the luminaire	59,8lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	50 000h
Ta Rated temperature	+25°C
Inrush current	150mA/500µs

## Spare parts

06720003	Lens.
ZS718zx0014	Service set.

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

## Indexes

Index	Color	RAL
718AL	ALUMINIUM	9006
718GR	GRAPHITE	7016
718W	WHITE	9003