



## Type of luminaire

Type of luminaire	Pole luminaire.
Photometric body	Indirect symmetrical light.

## General information

Materials	Powder painted aluminum cast. Lens - safety glass, transparent. Silicone gasket.
Type of light source	LED module, power supply Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.
Light control	Non-dimmable luminaire
Net / gross weight of luminaire	7,15kg / 9,65kg
Box dimensions [cm]	80x62x62
Side area of luminaire	0,1m <sup>2</sup>

## Technical data

LED module	Philips SLM C 830 1211 L19 2828 G7
Driver	Philips Xitanium 36W/m 929001486006 (↗ Datasheet)
Light source wattage	33,9W
Luminaire wattage	36,4W
Lamp luminous flux	5127lm
Luminaire luminous flux	3190lm
Light source efficiency	151,2lm/W
Efficiency of the luminaire	87,6lm/W
ULOR	6,84%
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>50 000h
Power Factor luminaire	PF 0,97
Ta Rated temperature	+25°C
Max ambient temperature	+35°C

This product contains light source of energy efficiency class **D**

Inrush current	4,6A / 65µs
----------------	-------------

## Spare parts

ZS777zx0016	Service set.
-------------	--------------

## Files to download

Photometric LDT files	Photometric IES files
Manual	BIM Revit
BIM ArchiCAD	

## Indexes

Index	Color	RAL
777AL	ALUMINIUM	9006
777GR	GRAPHITE	7016