



Type of luminaire

Type of luminaire	Wall luminaire.
Photometric body	Diffused, uncovered light.
Characteristics of the luminaire	Modern design plafon type luminaire.

General information

Materials	Base - powder painted aluminum cast. Front - stainless steel, hot dip galvanized steel, powder coated steel. Lens - safety glass, satin. Silicone gasket.
Mounting method	Fixing of the luminaire: 2 holes \varnothing 4,5mm, spacing 138x50mm.
Terminal	Connection terminals: max 3x2,5mm ² , possibility to connect luminaire in loop max 3x1,5mm ² . A round wire in the isolation with a diameter of \varnothing 7...10,5mm.
Type of light source	LED module, power supply
Light control	Trailing edge dimming
Net / gross weight of luminaire	3,1kg / 3,8kg
Box dimensions [cm]	27,5x22,8x33,5

Technical data

LED module	Philips LED Strip 0.5ft 550lm 830 FC HV4
Light source wattage	4W
Luminaire wattage	5,2W
Lamp luminous flux	648lm
Light source efficiency	162lm/W
Color temperature	3000K
Colour consistency (McAdam ellipse)	SDCM3
Colour rendering index CRI	80
Rated life time L70/B50 at 25°C	>70 000h
Energy Efficiency Index	A++
Power Factor luminaire	PF > 0,9
Ta Rated temperature	+25°C
Inrush current	1A/15,2 μ s

Maximum number of luminaires of this type per MCB:

B 10A: 157, **B 16A:** 250, **C 10A:** 260, **C 16A:** 425

Spare parts

06660005	Lens.
08652663	Gasket.
46999609	LED module.
46999746	Power supply.

Files to download

Manual

Indexes

Index	Color	RAL
668B	BLACK	9005
668GA	GALVANIZED	-
668ST	STAINLESS STEEL	-